



# Shrink Wrappers



## SHRINK TECH SYSTEMS


### SYSTEMS FEATURES

- \* Variable speed VFD conveyors (10 to 100 fpm)
- \* Change over made simple using Command Center and scales
- \* Variable speed film feed system and scrap take-up
- \* Easy load film cradle for CF film( Optional Centerfolder )
- \* STS Maintenance Mode for custom product set up
- \* Soft Start | Soft Stop
- \* Safety interlock guarding



### OPERATOR COMMAND CENTER

The Operator Command Center is conveniently located and features a 6" TouchScreen display with a 5 button direct access machine control for simple setup. Command Center also has 3 Operational Mode Backlit Screens and capability of storing ten product presets.



### "UNIVERSAL" SIDE SEAL

"Integrated" solid knife cross seal, side seal system ensures center line sealing at all times. Sealing area is protected by interlocked safety guarding.

### SYSTEMS SPECIFICATIONS:

	PACKAGE SIZE			MACHINE SIZE		
	W	H	L	W	L	H
<b>Models</b> STS 17	2" to 16"	to 8"	INFINITE	43"	91"	60"
STS 22	4" to 21"	to 8"	INFINITE	51"	100"	60"
STS 30	10" to 29"	to 8"	INFINITE	64"	108"	60"

ELECTRICAL: 120 volt, 15 amps AIR: 1CFM @ 80 psi  
 PKG. SPEED: up to 60 p/p/m CONVEYOR HEIGHT: 34" to 36"