

## Sealmaster

This table model impulse sealer is pedal operated, so that both hands can be used for sealing. By pressing the foot pedal the seal arm comes down and the machine starts sealing. A green light indicates the sealing time, after sealing and manually cooling, the foot pedal can be released. The sealing time of the Sealmaster can be adjusted, depending on the thickness of the foil. When using tubular foil, different sizes of bags can be made. The excess foil lengths can be cut off with the shielded cutting device which is integrated in the seal arm. The machine can work with all kinds of thermoplastic foils (polyethylene, polypropylene, PVC and thin laminates).

**Applications:** spare parts, films, CD's, pens, electronics, etc.



Sealmaster 300, 421, 620 SA



421 SA + RL 421 + OTST 421

Technical specifications	300 SA	421 SA	620 SA
Seal length	± 300 mm	± 420 mm	± 620 mm
Seal width	± 3 mm	± 3 mm	± 3 mm
Film thickness	Max. 2x0,2 mm	Max. 2x0,2 mm	Max. 2x0,2 mm
Voltage *	230 V/50-60 Hz	230 V/50-60 Hz	230 V/50-60 Hz
Consumption	750 W	550 W	700 W
Dimensions of packed machine	55x27x30 cm	68x26x30 cm	86x27x30 cm
Weight of machine	± 13 kg	± 15 kg	± 19 kg

\* The machines are also available in 115V on request

Accessories:			
Technical specifications	300 SA	421 SA	620 SA
Work table	OTST 321	OTST 421	OTST 621
Rolloflux	RL 321	RL 421	RL 621
Support + foot pedal	SP 321	SP 421	SP 621
Set of rolls	SR 321	SR 421	SR 621
Code seal	Unchangeable text in seal like your company name, special code etc.		

## Sealmaster & Magneta Accessories

The poly lock (PL) is an accessory that is mounted on the back of the machine in order to grip the tubular film in between two seals to avoid the film falling from the machine when a support with a set of rolls is used. This accessory can be ordered separately but is also packed in the accessories rolloflux and in the set of rolls.

The support (SP) is a stand the Magneta can be mounted on. With the stand comes a foot pedal, which allows the operator to keep his hands free for handling the bag. By pushing the foot pedal the sealing cycle will start.

A set of rolls for the support stand can be ordered separately. (SR) A polylock is supplied with this option.

Work table (OTST). The work table is equipped with an adjustable bag holder, to easily handle different bag sizes.

The rolloflux (RL) includes a polylock.



Accessories					
Worktable, length 350 mm <sup>1</sup>	<b>OTST 321</b>	<b>OTST 421</b>	<b>OTST 621</b>	<b>OTST 821</b>	<b>OTST 1021</b>
with adjustable support <sup>2</sup>	length 250 mm	length 350 mm	length 350 mm	length 250 mm	length 250 mm
packaging carton (cm)	44 x 27 x 6	57 x 37 x 6	76 x 37 x 6	96 x 27 x 6	116 x 27 x 6
Weight	2,8 kg	4,2 kg	5,4 kg	5,4 kg	6 kg
Rolloflux & poly lock	<b>RL 321</b>	<b>RL 421</b>	<b>RL 621</b>	<b>RL 821</b>	<b>RL 1021</b>
Packaging carton (cm)	48 x 10 x 10	60 x 10 x 10	82 x 10 x 10	99 x 10 x 10	120 x 10 x 10
Weight	1,5 kg	2 kg	2,6 kg	5 kg	5,8 kg
Support with foot pedal <sup>3</sup>	<b>SP 321</b>	<b>SP 421</b>	<b>SP 621</b>	<b>SP 821</b>	<b>SP 1021</b>
packaging carton (cm)	86 x 57 x 7	86 x 57 x 7	86 x 57 x 7	106 x 56 x 7	133 x 56 x 8
Weight	8 kg	8,4 kg	9 kg	10 kg	11,4 kg
Set of rolls <sup>4</sup> and poly lock <sup>5</sup>	<b>SR 321</b>	<b>SR 421</b>	<b>SR 621</b>	<b>SR 821</b>	<b>SR 1021</b>
packaging carton (cm)	48 x 10 x 10	60 x 10 x 10	82 x 10 x 10	105 x 10 x 10	120 x 10 x 10
Weight	1,2 kg	1,6 kg	2,6 kg	4,6 kg	5,1 kg